

Index

No.	Description	Remarks	Q'ty
1	Body	Aluminum, Steel Plate	1
2	FIre Alarm Lamp	LED (red)	1
3	Detector Activation Lamp	LED (red)	1
4	Power Indication Lamp	LED (green)	1
5	Fault Indication Lamp	LED (yellow)	1
6	Power Switch		1
7	Reset Switch	Non-latch type	1
8	Terminals	16P, M3	1
9	Power input terminal	2P, M3	1
10	Earth Terminal	M4	1

Specifications

Safety Standard	:	ETL Approved (ULSTD61010-1) KC mark EMC Certificated
Rated Voltage	:	DC24V/AC24V (50/60Hz)
Rated Current	:	Standby : 0.9VA (DC24V) Alarm : 2.2VA (DC24V)
	:	Standby : 1.6VA (AC24V) Alarm : 3.4VA (AC24V)
Alarm Sound	:	Buzzer
Relay Contact rating	:	DC30V, 1A/AC125V, 0.3A
Detector Power Voltage	:	DC19V (L+, C)
Wiring resistance	:	20 ohm or less (L+, C)
End of Line Resistor	:	7.5 kohm, 1/4W
Max number of detectors	:	Up to 20 pcs
Applicable Temperature	:	0℃ ~ +60℃

RoHS compliant

NITTAN COMPANY, LIMITED			
SCALE	Free	DATE	MAY. 22, 2023
MODEL NO.	CPC-4-24		
TITLE	Controller for OKB3 (Input DC24V)		
DRAWING NO.	E1520094-K	DIM.	mm