



Index

No.	Description	Remarks	Q'ty
1	Body	Aluminum, Steel Plate	1
2	Fire Alarm Lamp	LED (red)	1
3	Detector Activation Lamp	LED (red)	1
4	Power Indication Lamp	LED (green)	1
5	Fault Indication Lamp	LED (yellow)	1
6	Digital Indicator	Sensor Address /Err.Code	1
7	Power Switch	Latch type	1
8	Reset Switch	Non-latch type	1
9	Mode Switch	Slide type	1
10	Incrementa Switch	Non-latch type	1
11	Decrement Switch	Non-latch type	1
12	Audible Sound Stop Switch	Non-latch type	1
13	Terminals	16P, M3	1
14	Power input terminal	2P, M3	1
15	Earth Terminal	M4	1

Specifications

Safety Standard	:	ETL Approved (ULSTD61010-1)
	:	KC mark EMC Certified
Rated Voltage	:	AC100~240V (50/60Hz)
	:	Standby : 1.6VA (AC100V)
	:	Alarm : 3.2VA (AC100V)
Rated Current	:	Standby : 2.8VA (AC240V)
	:	Alarm : 4.7VA (AC240V)
Alarm Sound	:	Buzzer
Relay Contact rating	:	DC30V, 1A/AC125V, 0.3A
Detector Power Voltage	:	DC19V (L+, C)
Wiring resistance	:	20 ohm or less (L+, C)
Max number of detectors	:	Up to 20 pcs
Applicable Temperature	:	0℃ ~ +60℃
RoHS compliant		

NITAN COMPANY, LIMITED			
SCALE	Free	DATE	May. 23, 2023
MODEL NO.	CPC-4A		
TITLE	Addressable Controller for OKB3 (Input AC100~240V)		
DRAWING NO.	E1520095-K	DIM.	mm