



Index

No.	Description	Remarks	Q'ty
1.	Main Body	Flame Retardant Resin	1
2.	Smoke Inlet		6
3.	360° LED Indicator		1

Specifications

System Voltage	: 35 VDC
Operating Voltage Range	: 20 VDC to 38 VDC Peak
Standby Current	: 200 μ A
Alarm Current (with red LED)	: 6mA
360° LED Indicator	: Standby - Green LED Flash Alarm - Red LED Light
Sensitivity	: 1.06 %/Ft. to 1.9 %/Ft.
Applicable Standard	: UL268 7th Edition
UL Ambient Installation Temperature	: 0 $^{\circ}$ C (32 $^{\circ}$ F) to +38 $^{\circ}$ C (100 $^{\circ}$ F)
Storage Temperature	: -40 $^{\circ}$ C (-40 $^{\circ}$ F) to +70 $^{\circ}$ C (158 $^{\circ}$ F)
Maximum Relative Humidity	: Up to 95%RH, non-condensing
Environment	: Indoor dry use only

NITAN COMPANY, LIMITED

SCALE	1 / 2	DATE	July 29, 2022
MODEL NO.	EVA-PY3		
TITLE	Addressable Photoelectric Smoke Detector		
DRAWING NO.	N0100025	Dim:	mm